

TRU-SLEEVE ANCHORS

TRU-SLEEVE ANCHORS



- Electro galvanized
- For fixing into concrete and rock
- Anchor thread size equals hole size to be drilled into concrete
- Non-bottom bearing. Does not require precise hole depth.
- Supplied complete with nut and washer.
- Pre-assembled. Just insert and tighten.
- Drill size equals anchor size. Insert through object to be fastened and tighten.

Load Capacity in 24 Mpa Concrete

Ref	Anchor Size & Hole	Anchor Length	M.M Thread	Pull-Out (Kgs)	Shear (Kgs)	Min. Depth
SA 81	8 mm	40 mm	6	1150	900	35 mm
SA 82	8 mm	65 mm				35 mm
SA 83	8 mm	85 mm				35 mm
SA 101	10 mm	50 mm	8	1800	1400	45 mm
SA 102	10 mm	77 mm				45 mm
SA 103	10 mm	97 mm				45 mm
SA 121	12 mm	60 mm	10	2800	2050	50 mm
SA 122	12 mm	75 mm				50 mm



SA 123	12 mm	99 mm				50 mm
SA 161	16 mm	65 mm	12	3700	3100	55 mm
SA 162	16 mm	111 mm				55 mm

SPACE, EDGE AND END DISTANCE RECOMMENDATIONS				
Anchor Size mm	8	10	12	16
Spacing Distance mm	65	65	90	110
Edge and End Distance mm Load Parallel or Away From Edge	45	50	65	75
Load Toward Edge	60	70	90	105