

NM1 "S" RANGE MOULDED CASE CIRCUIT BREAKERS

CODE.	RATED CURRENT	KA RATING	DIMENSIONS (MM)
NM1-125S	16A,20A,32A,40A,50A,63A,80A,100A	25kA	155(L) x 90(W) x 63(D)
NM1-250S	125A,150A,160A,200A,225A,250A	25kA	165(L) x 105(W) x 86(D)
NM1-400S	250A,315A,350A,400A	25kA	258(L) x 140(W) x 104(D)
NM1-630S	500A,630A	25kA	270(L) x 182(W) x 160(D)



NM1 "H" RANGE MOULDED CASE CIRCUIT BREAKERS

CODE.	RATED CURRENT	KA RATING	DIMENSIONS (MM)
NM1-125H	16A,20A,32A,40A,50A,63A,80A,100A	50kA	155(L) x 90(W) x 86(D)
NM1-250H	125A,150A,160A,200A,225A,250A	50kA	165(L) x 105(W) x 103(D)
NM1-400H	250A,315A,350A,400A	60kA	257(L) x 150(W) x 107(D)
NM1-630H	500A,630A	65kA	270(L) x 182(W) x 111(D)
NM1-800H	630A,700A,800A	65kA	280(L) x 210(W) x 107(D)
NM1-1250H	1000A,1250A	65kA	406(L) x 210(W) x 141(D)



NM1 4 POLE MOULDED CASE CIRCUIT BREAKERS

CODE.	RATED CURRENT	KA RATING	DIMENSIONS (MM)
NM1-125H/4	16A,20A,32A,40A,50A,63A,80A,100A	50kA	155(L) x 120(W) x 86(D)
NM1-250H/4	125A,150A,160A,200A,225A,250A	50kA	165(L) x 140(W) x 103(D)
NM1-400S/4	250A,315A,350A,400A	60kA	257(L) x 198(W) x 104(D)
NM1-630S/4	500A,630A	65kA	270(L) x 240(W) x 111(D)
NM1-800H/4	630A,700A,800A	65kA	276(L) x 280(W) x 109(D)
NM1-1250H/4	1000A,1250A	65kA	406(L) x 280(W) x 141(D)



VARI-DEPTH DOOR INTERLOCKED HANDLES

CODE.	APPLICABLE RANGE	DESCRIPTION
NM1-VDH-125S	NM-100S RANGE	300MM SHAFT
NM1-VDH-250S	NM-250S RANGE	300MM SHAFT
NM1-VDH-400S	NM-400S RANGE	300MM SHAFT
NM1-VDH-630S	NM-630S RANGE	300MM SHAFT
NM1-VDH-800H	NM-800S RANGE	300MM SHAFT
NM1-VDH-1250H	NM-1250S RANGE	300MM SHAFT

SHUNT TRIPS

CODE.	APPLICABLE RANGE	VOLTAGES
NM1-ST-125S	NM1-100S	100V / 230V / 400V / 550V
NM1-ST-250S	NM1-250S	100V / 230V / 400V / 550V
NM1-ST-400S	NM1-400S	100V / 230V / 400V / 550V
NM1-ST-630S	NM1-630S	100V / 230V / 400V / 550V
NM1-ST-800H	NM1-800H	100V / 230V / 400V / 550V
NM1-ST-1250H	NM1-1250H	100V / 230V / 400V / 550V

AUXILIARY CONTACTS

CODE.	APPLICABLE RANGE	VOLTAGES
NM1-AS-125S	NM1-100S	1NO & 1NC AUXILIARY CONTACT
NM1-AS-250S	NM1-250S	1NO & 1NC AUXILIARY CONTACT
NM1-AS-400S	NM1-400S	1NO & 1NC AUXILIARY CONTACT
NM1-AS-630S	NM1-630S	1NO & 1NC AUXILIARY CONTACT
NM1-AS-800R	NM1-800H	1NO & 1NC AUXILIARY CONTACT
NM1-AS-1250R	NM1-1250H	1NO & 1NC AUXILIARY CONTACT

UNDERVOLTAGE RELEASE

CODE.	APPLICABLE RANGE	VOLTAGES
NM1-AS-125S	NM1-100S	RATED VOLTAGE OF THE UVT IS 50HZ, 230V & 400V
NM1-AS-250S	NM1-250S	
NM1-AS-400S	NM1-400S	
NM1-AS-630S	NM1-630S	
NM1-AS-800R	NM1-800H	
NM1-AS-1250R	NM1-1250H	

KEY LOCKOUTS - KEY REMOVABLE IN BOTH POSITIONS

CODE.	APPLICABLE RANGE	VOLTAGES
NM1-KEY	KEYED ALIKE	KEY LOCKOUT FOR NM1-250S UP TO NM1-1250H