

NAIL-IN ANCHORS

NAIL-IN ANCHORS



Ref	Size	Hole	Min. Depth	Fix Material
NA 51	5 x 36	5 mm	25 mm	6 mm
NA 52	5 x 45	5 mm	25 mm	6 mm
NA 62	6 x 35	6 mm	25 mm	6 mm
NA 63	6 x 55	6 mm	30 mm	25 mm
NA 64	6 x 70	6 mm	35 mm	35 mm
NA 80	8 x 60	8 mm	45 mm	15 mm
NA 81	8 x 80	8 mm	45 mm	35 mm



NA 82	8 x 100	8 mm	50 mm	50 mm
NA 83	8 x 120	8 mm	50 mm	70 mm

Many applications where good quality lightweight fastenings are required.

Partition profile rails.

**Wall flashings. Skirting fixings. Timber battens. Security spikes, Cable saddles, Cables ducts
Brackets, Copings**

- Flat head for flush fixings
- Pin manufactured from EN 8 Hi-tensile steel
- Buttress thread, easy to drive in – screw out
- Double yellow passivated – better rust prevention
- Reinforced head – better holding power
- Ribs – for securing material fit
- Internal locking rings – prevent screw expanding plug prematurely
- Correct material mix – will not become brittle in dry conditions or soft in damp conditions, ideal for South African changing climate
- Reinforced valley – strengthens anchor body
- Locking lugs – prevent dust in hole causing premature expansion when inserting
- Long even expansion – 50% more surface grip

